# NSN 5930-00-543-1219

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-543-1219

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

2.125 inches

## **Overall Height:**

1.312 inches

## **Overall Width:**

1.250 inches

## Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

1.000 inches single actuator

## **Nonturn Device Radius:**

# 0.531 inches at 3: 00 o'clock

## Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

# **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

2 each section rear

## **Throw Quantity:**

4 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-543-1219

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Style Designator: Circular wafer, bushing mount Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0