

View Online at <https://aerobasegroup.com/nsn/5930-00-543-1238>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.780 inches

Overall Height:

1.346 inches

Overall Width:

0.656 inches

Bushing Length:

Between 0.355 inches and 0.385 inches

Body Length:

Between 0.765 inches and 0.795 inches

Body Width:

0.656 inches

Body Height:

Between 0.651 inches and 0.661 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.105 inches and 0.135 inches

Actuator Height:

Between 0.305 inches and 0.335 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0