

View Online at <https://aerobasegroup.com/nsn/5930-00-543-1238>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.780 inches

**Overall Height:**

1.346 inches

**Overall Width:**

0.656 inches

**Bushing Length:**

Between 0.355 inches and 0.385 inches

**Body Length:**

Between 0.765 inches and 0.795 inches

**Body Width:**

0.656 inches

**Body Height:**

Between 0.651 inches and 0.661 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.105 inches and 0.135 inches

**Actuator Height:**

Between 0.305 inches and 0.335 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position momentary

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0