NSN 5930-00-543-8205

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-543-8205

Overall Length: 4.250 inches Overall Height: 3.125 inches Overall Width: 3.625 inches Body Diameter: 3.000 inches Unthreaded Mounting Hole Diameter: 0.203 inches Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Optaring Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Fracture Sprovided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 13.000 pounds per square inch Thread Size 0.250 inches single pressure connection Mounting Facility Pattern: Two position in-line
Overall Heigh: 3.125 inches Overall Width: 3.625 inches Body Diameter: 3.000 inches Unthreaded Mounting Hole Diameter: 0.203 inches Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Operating Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (pi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 13.0.00 pounds per square inch Thread Size: 0.250 inches single pressure connection
A125 inches Overall Width: 3.625 inches Body Diameter: 3.000 inches Unthreaded Mounting Hole Diameter: 0.203 inches Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Operating Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection
Overall Width:3.625 inchesBody Diameter:3.000 inchesUnthreaded Mounting Hole Diameter:0.203 inchesDistance Between Mounting Facility Centers:3.000 inchesPressure Switch Type:GageOparting Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:13.0.00 pounds per square inchThread Size:0.250 inches single pressure connectionKounting Facility Pattern:
3.625 inchesBody Diameter:3.000 inchesUnthreaded Mounting Hole Diameter:0.203 inchesDistance Between Mounting Facility Centers:3.000 inchesPressure Switch Type:GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Eracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchChread Size:0.250 inches single pressure connectionKounting Facility Pattern:
Body Diameter:3.000 inchesUnthreaded Mounting Hole Diameter:0.203 inchesDistance Between Mounting Facility Centers:3.000 inchesPressure Switch Type:GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:13.0.00 pounds per square inchChread Size:0.250 inches single pressure connectionKonting Facility Pattern:
3.000 inches Unthreaded Mounting Hole Diameter: 0.203 inches Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Operating Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 13.000 pounds per square inch Thread Size: 0.250 inches single pressure connection
Uthreaded Mounting Hole Diameter:0.203 inchesDistance Between Mounting Facility Centers:3.000 inchesPressure Switch Type:GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:13.00 pounds per square inchChread Size:0.250 inches single pressure connectionKurting Facility Pattern:
0.203 inches Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Operating Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Cty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection
Distance Between Mounting Facility Centers: 3.000 inches Pressure Switch Type: Gage Operating Tempurature Rating: Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection
3.000 inchesPressure Switch Type:GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
Pressure Switch Type:GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holePeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
GageOperating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitBounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portChready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
Operating Tempurature Rating:Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheitMounting Method:Bracket and unthreaded holeFeatures Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Bracket and unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Features Provided:Electrical access portThready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Thready Qty Per Inch (tpi):18 single pressure connectionContact Action Stimulus:IncreaseProof Pressure:130.00 pounds per square inchThread Size:0.250 inches single pressure connectionMounting Facility Pattern:
18 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Contact Action Stimulus: Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Increase Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Proof Pressure: 130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
130.00 pounds per square inch Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
Thread Size: 0.250 inches single pressure connection Mounting Facility Pattern:
0.250 inches single pressure connection Mounting Facility Pattern:
Mounting Facility Pattern:
Two position in-line
•
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
7.5 amperes resistive load single voltage
7.5 amperes resistive load single voltage Contact Adjustability:
Contact Adjustability:
Contact Adjustability: Deactuation point adjustable and actuation point adjustable

External deactuation point screw and external actuation point screw

NSN 5930-00-543-8205

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0