NSN 5930-00-543-8825

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-543-8825

| Hazardous Locations/environmental Protection: |
|---|
| Watertight |
| Overall Height: |
| 7.812 inches |
| Overall Width: |
| 5.500 inches |
| Shaft Diameter: |
| 0.625 inches single actuator |
| Shaft Length: |
| 1.000 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.328 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 00289 |
| Knob Manufacturer Part Number: |
| Ms2rev1no7 |
| Longest Horizontal Distance Between Mounting Centers: |
| 8.625 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 4.000 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 1 each section front |
| Mounting Method: |
| Base single mounting facility |
| Features Provided: |
| Actuator knob and metallic inclosure |
| Contact Voltage Rating In Volts: |
| 450.0 ac at sea level |
| Switch Actuator Momentary Position: |
| Clockwise single actuator |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Shaft Type: |

Round single actuator

NSN 5930-00-543-8825 Rotary Switch - Page 2 of 2



| Terminal Type: |
|---|
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 30.0 amperes resistive load ac at sea level |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A052b0