## NSN 5930-00-543-8888

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-543-8888 **Body Style:** Hole mounted **Overall Length:** 1.124 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Width:** 0.625 inches **Body Length:** 1.094 inches **Body Width:** 0.625 inches **Body Height:** 1.094 inches **Unthreaded Mounting Hole Diameter:** Between 0.064 inches and 0.070 inches **Actuator Style:** Round **Maximum Voltage Rating In Volts:** 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** Between 6.0 ounces and 14.0 ounces **Actuator Movement:** Between 0.047 pretravel inches and 0.031 overtravel inches and 0.006 differential inches and 0.016 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes inductive dc **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5930-00-543-8888

Sensitive Switch - Page 2 of 2



Fiig:

A053a0