## NSN 5930-00-544-5537

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-544-5537

#### **Body Style:**

Hole mounted

#### Hazardous Locations/environmental Protection:

Industrial use

## Actuator Style:

Round

## Actuator Diameter:

0.490 inches

#### Actuator Height:

0.500 inches

Housing Height:

#### 3.563 inches

#### Housing Length:

4.938 inches

#### Housing Width:

#### 3.250 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.438 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

## Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

## Inclosure Type:

Fully enclosed

## **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

## Switch Release Force:

64.0 inch-ounces

#### Switch Actuating Force:

204.0 inch-ounces

#### Actuator Movement:

13.0 pretravel degrees and 30.0 overtravel degrees and 10.0 differential degrees

#### Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

## Terminal Type And Quantity:

8 screw

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-544-5537

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

