

View Online at <https://aerobasegroup.com/nsn/5930-00-548-1184>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

1.890 inches

Overall Height:

Between 0.865 inches and 0.885 inches

Overall Width:

Between 0.865 inches and 0.885 inches

Body Diameter:

Between 0.552 inches and 0.572 inches

Bushing Length:

Between 0.422 inches and 0.454 inches

Body Length:

0.625 inches

Case Material:

Metal

Actuator Diameter:

Between 0.408 inches and 0.428 inches

Actuator Height:

Between 0.235 inches and 0.265 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0