

View Online at <https://aerobasegroup.com/nsn/5930-00-548-1184>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

1.890 inches

**Overall Height:**

Between 0.865 inches and 0.885 inches

**Overall Width:**

Between 0.865 inches and 0.885 inches

**Body Diameter:**

Between 0.552 inches and 0.572 inches

**Bushing Length:**

Between 0.422 inches and 0.454 inches

**Body Length:**

0.625 inches

**Case Material:**

Metal

**Actuator Diameter:**

Between 0.408 inches and 0.428 inches

**Actuator Height:**

Between 0.235 inches and 0.265 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0