

View Online at <https://aerobasegroup.com/nsn/5930-00-548-1437>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.600 inches

Body Width:

0.610 inches

Body Height:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Actuator Style:

Round

Actuator Diameter:

0.195 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.762 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

0.078 pretravel inches and 0.068 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 200.000 milliamperes inductive dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0