

View Online at <https://aerobasegroup.com/nsn/5930-00-548-3274>

Hazardous Locations/environmental Protection:

Dustproof

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.188 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.312 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.312 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0