

View Online at <https://aerobasegroup.com/nsn/5930-00-548-3274>

**Hazardous Locations/environmental Protection:**

Dustproof

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.188 inches single actuator

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

2.312 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.312 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

7 each section front

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0