NSN 5930-00-548-3343

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-3343

| Threa | d I | Len | gth: |
|-------|-----|-----|------|
| | | | |

0.438 inches single mounting facility

First Flat Length:

0.375 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.812 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

14 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 dc at sea level

Switch Actuator Indexing Position Quantity:

14 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

25.7 degrees single actuator

Contact Load Current Rating:

25.0 milliamperes resistive load dc at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-00-548-3343Rotary Switch - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A052b0