## NSN 5930-00-548-3489

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-3489 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 3.844 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** Between 0.432 inches and 0.442 inches **Overall Height:** 1.312 inches **Overall Width:** 0.625 inches **Body Width:** 0.625 inches **Body Height:** 1.312 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 0.995 inches and 1.005 inches **Actuator Style:** Round **Actuator Height:** Between 0.890 inches and 0.922 inches **Actuator Position-action Relationship:** Up position maintained and down position momentary and center position maintained **Maximum Voltage Rating In Volts:** 48.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 2c 1st position **Thread Size:** 0.112 inches **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc **Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

14 tab, solder lug

## NSN 5930-00-548-3489

Lever Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0