

View Online at <https://aerobasegroup.com/nsn/5930-00-548-3573>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.609 inches

**Overall Height:**

Between 1.047 inches and 1.077 inches

**Overall Width:**

Between 1.047 inches and 1.077 inches

**Bushing Length:**

Between 0.250 inches and 0.280 inches

**Body Length:**

0.687 inches

**Actuator Diameter:**

Between 0.360 inches and 0.390 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 15.000 amperes inductive ac

**Test Data Document:**

97151-66b3850 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0