

View Online at <https://aerobasegroup.com/nsn/5930-00-548-3619>

Thread Class:

2a single mounting facility

Thread Length:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

Between 1.595 inches and 1.640 inches

Overall Height:

Between 1.860 inches and 1.890 inches

Overall Width:

Between 1.547 inches and 1.577 inches

First Flat Length:

0.235 inches single actuator and 0.265 inches single actuator

Flat Height:

0.203 inches single actuator and 0.233 inches single actuator

Shaft Diameter:

0.235 inches single actuator and 0.265 inches single actuator

Shaft Length:

0.735 inches single actuator and 0.765 inches single actuator

Nonturn Device Radius:

0.516 inches at 6: 00 o'clock and 0.546 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 dc at sea level

Shaft Flat/slot Angular Location:

330.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.5 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0