NSN 5930-00-548-4218

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-421
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.078 inches
Overall Height:
2.828 inches
Overall Width:
2.828 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.000 inches single actuator
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Knob Specificationial Markings:
Arrow
Longest Horizontal Distance Between Mounting Centers:
2.312 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.312 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Threaded hole single mounting facility
Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

NSN 5930-00-548-4218Rotary Switch - Page 2 of 2



Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
120.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0