

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4239>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.390 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.087 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.092 inches

**Actuator Height:**

0.020 inches

**Actuator Free Position Height:**

0.330 inches

**Maximum Voltage Rating In Volts:**

220.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

0.020 pretravel inches and 0.005 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0