

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4267>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Pressure proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Body Length:

2.000 inches

Body Width:

0.703 inches

Body Height:

1.200 inches

Case Material:

Metal

Actuator Length:

Between 0.907 inches and 0.937 inches

Actuator Style:

Leaf

Actuator Free Position Height:

Between 0.515 inches and 0.545 inches

Maximum Voltage Rating In Volts:

115.0 ac and 120.0 dc

End Application:

Helicopter iroquois uh-1

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 22.0 ounces and 28.0 ounces

Actuator Movement:

0.085 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Precious Material And Location:

Contact surfaces silver

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0