

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4267>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Pressure proof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Body Length:**

2.000 inches

**Body Width:**

0.703 inches

**Body Height:**

1.200 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.907 inches and 0.937 inches

**Actuator Style:**

Leaf

**Actuator Free Position Height:**

Between 0.515 inches and 0.545 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 120.0 dc

**End Application:**

Helicopter iroquois uh-1

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 22.0 ounces and 28.0 ounces

**Actuator Movement:**

0.085 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

**Precious Material And Location:**

Contact surfaces silver

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0