NSN 5930-00-548-4452

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-4452

Thr	ead Class:
2a	
Boo	ly Style:
Bus	hing mounted
Haz	ardous Locations/environmental Protection:
Fun	gus proof
Ove	rall Length:
1.28	1 inches
Ove	rall Height:
0.87	75 inches
Ove	rall Width:
0.87	'5 inches
Boo	ly Diameter:
0.56	2 inches
Bus	hing Length:
0.37	'5 inches
Bod	ly Length:
0.40	5 inches
Act	uator Style:
Rou	nd, stepped
Act	uator Diameter:
0.37	'5 inches
Act	uator Height:
0.12	25 inches
Act	uator Color:
Blac	k single actuator
Max	imum Voltage Rating In Volts:
230	0 ac and 24.0 dc
Incl	osure Type:
Full	y enclosed
Μοι	Inting Method:
Thre	eaded bushing
Thre	eady Qty Per Inch (tpi):
27	
Thr	ead Size:
0.62	25 inches
Nor	pile-up Contact Arrangement:
1 pc	le, single throw, normally open, momentary action single switch
Cor	tact Load Current Rating At Maximum Rated Voltage:
17.0	000 amperes resistive dc and 7.500 amperes resistive ac
Spe	cial Features:
•	

unit

Incl rubber boot

NSN 5930-00-548-4452

Push Switch - Page 2 of 2

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

