NSN 5930-00-548-4508

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-4508

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

First Flat Length:

0.500 inches single actuator

Flat Height:

0.157 inches single actuator

Shaft Diameter:

0.188 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

1.719 inches

Individual Section Quantity:

6

Knob Manufacturer Code:

81352

Knob Manufacturer Part Number:

An3220

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

7 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

NSN 5930-00-548-4508

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Special Features:

Silver-plated contact finish

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0