

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4585>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Fungus proof

**Overall Length:**

1.875 inches

**Overall Height:**

1.297 inches

**Body Length:**

1.219 inches

**Body Width:**

0.516 inches

**Body Height:**

1.297 inches

**Unthreaded Mounting Hole Diameter:**

0.138 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Actuator Style:**

Round

**Actuator Height:**

0.359 inches

**Actuator Free Position Height:**

0.359 inches

**Actuator Adapter Style:**

Roller leaf

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.078 overtravel inches and 0.172 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Special Features:**

Switch has 6-32 nc-2 tapped hole 5/16 in. Min depth in end of shaft

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0