

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4585>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Fungus proof

Overall Length:

1.875 inches

Overall Height:

1.297 inches

Body Length:

1.219 inches

Body Width:

0.516 inches

Body Height:

1.297 inches

Unthreaded Mounting Hole Diameter:

0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Height:

0.359 inches

Actuator Free Position Height:

0.359 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.188 pretravel inches and 0.078 overtravel inches and 0.172 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Special Features:

Switch has 6-32 nc-2 tapped hole 5/16 in. Min depth in end of shaft

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0