

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4612>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Overall Length:

Between 4.026 inches and 4.036 inches

First Flat Length:

0.495 inches single actuator and 0.505 inches single actuator

Flat Height:

0.215 inches single actuator and 0.218 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.255 inches single actuator

Shaft Length:

2.214 inches single actuator and 2.224 inches single actuator

Overall Diameter:

Between 1.995 inches and 2.005 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

4 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0