

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4630>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

4.625 inches

**Overall Height:**

1.938 inches

**Overall Width:**

1.625 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.187 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 10: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 10: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 2nd section front

**Throw Quantity:**

4 2nd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 2nd section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Special Features:**

Four dummy terminals on front of section one and eight dummy terminals on rear of section two

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0