

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4885>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.922 inches and 1.954 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Width:

Between 0.672 inches and 0.704 inches

Body Length:

Between 1.922 inches and 1.954 inches

Body Width:

Between 0.672 inches and 0.704 inches

Body Height:

1.156 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.150 inches and 0.154 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.359 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.156 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.094 overtravel inches and 0.020 differential inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0