

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4885>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 1.922 inches and 1.954 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Width:**

Between 0.672 inches and 0.704 inches

**Body Length:**

Between 1.922 inches and 1.954 inches

**Body Width:**

Between 0.672 inches and 0.704 inches

**Body Height:**

1.156 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.150 inches and 0.154 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.359 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.156 inches

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.094 overtravel inches and 0.020 differential inches and 0.050 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0