## NSN 5930-00-548-4893

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-4893

| Body Style:  |
|--|
| Hole mounted   |
| Overall Length:  |
| 1.940 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 1.000 inches   |
| Overall Height:  |
| 1.219 inches   |
| Overall Width:   |
| 0.687 inches   |
| Body Length:   |
| 1.940 inches   |
| Body Width:  |
| 0.687 inches   |
| Body Height:   |
| 1.040 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.140 inches   |
| Actuator Style:  |
| Leaf   |
| Actuator Width:  |
| 0.190 inches   |
| Actuator Free Position Height:   |
| 0.969 inches   |
| Maximum Voltage Rating In Volts:   |
| 480.0 ac and 250.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Unthreaded hole  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, one position momentary single switch unit  |
| Switch Release Force:  |
| 0.75 ounces  |
| Switch Actuating Force:  |
| 4.0 ounces   |
| Actuator Movement:   |
| Between 0.203 pretravel inches and 0.156 overtravel inches and 0.004 differential inches and 0.035 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac  |

3 screw

**Terminal Type And Quantity:** 

## NSN 5930-00-548-4893

Sensitive Switch - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0