

View Online at <https://aerobasegroup.com/nsn/5930-00-548-4936>

Hazardous Locations/environmental Protection:

Dustproof

First Flat Length:

0.531 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Facility Circle Radius:

1.875 inches single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

150.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0