

View Online at <https://aerobasegroup.com/nsn/5930-00-548-5158>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

Between 1.932 inches and 2.192 inches

**Overall Height:**

Between 1.296 inches and 1.328 inches

**Overall Width:**

Between 0.922 inches and 0.954 inches

**First Flat Length:**

0.370 inches single actuator and 0.380 inches single actuator

**Flat Height:**

0.213 inches single actuator and 0.223 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.807 inches single actuator and 0.817 inches single actuator

**Nonturn Device Radius:**

0.526 inches at 3:00 o'clock and 0.536 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-40.0/+55.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0