

View Online at <https://aerobasegroup.com/nsn/5930-00-548-5933>

Inside Diameter:

0.125 inches single connection

Overall Length:

3.813 inches

Overall Width:

4.063 inches

Body Diameter:

3.000 inches

Body Length:

2.281 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

25.50 actuation point pounds per square inch and 19.50 deactuation point pounds per square inch and 16.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0