NSN 5930-00-548-5933

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-5933

Inside Diameter:
0.125 inches single connection
Overall Length:
3.813 inches
Overall Width:
4.063 inches
Body Diameter:
3.000 inches
Body Length:
2.281 inches
Distance Between Mounting Facility Centers:
3.000 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
40.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
500.0 milliamperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
25.50 actuation point pounds per square inch and 19.50 deactuation point pounds per square inch and 16.00 differential point pounds per
square inch
Contact Voltage Rating In Volts:
30.0 dc at sea level single voltage
Pressure Connector Type:

Gas or liquid

Media For Which Designed:

Gasket seal, threaded internal single connection

NSN 5930-00-548-5933

Pressure Switch - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	•
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0