NSN 5930-00-548-5943

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-5943

Thread Class: 3a single pressure connection **Overall Length:** 4.375 inches **Overall Width:** 4.063 inches **Body Diameter:** 3.000 inches **Distance Between Mounting Facility Centers:** 3.000 inches **Pressure Switch Type:** Gage **Mounting Method: Bracket** Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 400.00 pounds per square inch **Thread Size:** 0.4375 inches single pressure connection **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained **Sensing Element Burst Pressure:** 600.00 pounds per square inch **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 0.5 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 25.00 actuation point pounds per square inch and 20.00 deactuation point pounds per square inch and 5.00 differential point pounds per square inch **Contact Voltage Rating In Volts:** 30.0 dc at sea level single voltage **Pressure Connector Type:**

Gas or liquid

Media For Which Designed:

Gasket seal, threaded internal single connection

NSN 5930-00-548-5943

Pressure Switch - Page 2 of 2



Styl			

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0