## NSN 5930-00-548-6603

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-6603 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.750 inches **Overall Height:** 2.828 inches **Overall Width:** 2.828 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.750 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Specificationial Markings:** Std oval **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 2 each section front **Mounting Facility Circle Radius:** 2.312 inches single mounting facility **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 120.0 dc at sea level

Four position circular single mounting facility

**Mounting Facility Pattern:** 

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

## **NSN 5930-00-548-6603** Rotary Switch - Page 2 of 2



Shaft Type:
Round, hollowed single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0