# NSN 5930-00-548-6636

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-6636

# **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

8.125 inches

## Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

#### Shaft Length:

6.687 inches single actuator

## **Overall Diameter:**

1.938 inches

**Nonturn Device Radius:** 

0.531 inches at 12: 00 o'clock

Individual Section Quantity:

#### 1

Nonturn Device Type:

Tab at 12: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

4 single section rear

## Throw Quantity:

2 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-548-6636

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

#### **Precious Material And Location:**

Contacts and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

## Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### **Demilitarization:**

No

#### Fiig:

A052b0