NSN 5930-00-548-6857

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-6857

Thread Class:

2b single mounting facility

Overall Length:

2.688 inches

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.907 inches single actuator and 0.967 inches single actuator

Overall Diameter:

1.375 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

NSN 5930-00-548-6857

Rotary Switch - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0