NSN 5930-00-548-6879

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-6879

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.593 inches **Shaft Diameter:** 0.249 inches single actuator **Shaft Length:** 0.375 inches single actuator **Overall Diameter:** 1.250 inches **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 single section rear **Throw Quantity:** 4 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Metallic inclosure **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 300.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:**

0.2 amperes resistive load ac at sea level

NSN 5930-00-548-6879

Rotary Switch - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0