## NSN 5930-00-548-6880

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-6880

## Thread Length:

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.625 inches single actuator

**Individual Section Quantity:** 

1

**Knob Manufacturer Code:** 

37942

**Knob Manufacturer Part Number:** 

366

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

4 single section rear

**Throw Quantity:** 

2 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob and metallic inclosure

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

6.0 lowest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load lowest ac voltage rating at sea level

**Thread Series Designator:** 

Unef single mounting facility

## NSN 5930-00-548-6880

Rotary Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0