NSN 5930-00-548-7012

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-548-7012

2b single mounting facility **Overall Length:** 4.968 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 1.125 inches single actuator **Individual Section Quantity:** 5 **Knob Manufacturer Code:** 82121 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 7 each section front **Mounting Facility Circle Radius:** 3.250 inches single mounting facility **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 lowest dc voltage rating at sea level **Mounting Facility Pattern:** Four position circular single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:** Tab w/screw

NSN 5930-00-548-7012

Rotary Switch - Page 2 of 2



Contact	Switching	Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level and 800.0 milliamperes inductive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0