## NSN 5930-00-548-7036

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7036 **Thread Class:** 2b single mounting facility **Overall Length:** 5.750 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 1.500 inches single actuator **Individual Section Quantity:** 7 **Knob Manufacturer Code:** 80064 **Knob Manufacturer Part Number:** S6202-73075-45 **Longest Horizontal Distance Between Mounting Centers:** 2.312 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.312 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 125.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator Shaft Type: Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.275 inches single actuator **Terminal Type:** Screw **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-00-548-7036

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

5.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contacts and rotors plated silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0