NSN 5930-00-548-7077

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7077

Thread Class: 2b single mounting facility **Overall Length:** 5.281 inches **Overall Height:** 4.750 inches **Overall Width:** 4.750 inches First Flat Length: 1.125 inches single actuator Flat Height: 0.312 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 2.375 inches single actuator **Unthreaded Mounting Hole Diameter:** 0.406 inches single mounting facility **Individual Section Quantity: Knob Manufacturer Code:** 10001 **Knob Manufacturer Part Number:** 9s5363 piece 6 **Longest Horizontal Distance Between Mounting Centers:** 3.781 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 3.781 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 4 each section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-00-548-7077Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0