NSN 5930-00-548-7077

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7077

Thread Class:

2b single mounting facility

Overall Length:

5.281 inches

Overall Height:

4.750 inches

Overall Width:

4.750 inches

First Flat Length:

1.125 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

2.375 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

9s5363 piece 6

Longest Horizontal Distance Between Mounting Centers:

3.781 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 each section front

Throw Quantity:

4 each section front

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-00-548-7077

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0