

NSN 5930-00-548-7499 Sensitive Switch - Page 1 of 2	AeroBase Group		
View Online at https://aerobasegroup.com/nsn/5930-00-548-7499			
Body Style:			
Hole mounted			
Overall Length:			
Between 1.344 inches and 1.406 inches			
Center To Center Distance Between Mounting Facilities Parallel To Length:			
Between 0.872 inches and 0.878 inches			
Overall Width:			
Between 0.496 inches and 0.534 inches			
Body Length:			
Between 1.344 inches and 1.406 inches			

Between 0.594 inches and 0.656 inches

Body Height:

Body Width:

Between 0.390 inches and 0.422 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

NSN 5930-00-548-7499

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0