

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7518>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

1.078 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

1.469 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.188 inches

**Actuator Free Position Height:**

1.188 inches

**Maximum Voltage Rating In Volts:**

600.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

Between 0.2 ounces and 0.7 ounces

**Switch Actuating Force:**

Between 1.0 ounces and 2.5 ounces

**Actuator Movement:**

Between 0.343 pretravel inches and 0.187 overtravel inches and 0.016 differential inches and 0.096 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac

**Special Features:**

Includes 11/64 diameter by 17/32 in plunger loosely riveted to leverarm actuator

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0