

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7521>

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Body Length:

1.937 inches

Body Width:

0.687 inches

Body Height:

0.953 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

2.437 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.344 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.187 inches

Maximum Voltage Rating In Volts:

250.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.219 pretravel inches and 0.031 overtravel inches and 0.080 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

300.000 milliamperes resistive dc and 200.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 200.000 milliamperes motor dc and 5.000 amperes resistive ac and 5.000 amperes motor ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0