

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7521>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Body Length:**

1.937 inches

**Body Width:**

0.687 inches

**Body Height:**

0.953 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

2.437 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.344 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.187 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

10.0 ounces

**Actuator Movement:**

Between 0.219 pretravel inches and 0.031 overtravel inches and 0.080 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

300.000 milliamperes resistive dc and 200.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 200.000 milliamperes motor dc and 5.000 amperes resistive ac and 5.000 amperes motor ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0