

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7938>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.094 inches

Overall Height:

9.625 inches

Overall Width:

9.500 inches

Mounting Slot Width:

0.531 inches single mounting facility

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

0.719 inches single actuator and 0.781 inches single actuator

Unthreaded Mounting Hole Diameter:

0.500 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

8.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and slot single mounting facility

Features Provided:

Dummy section

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, threaded hole single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Special Features:

Round, threaded hole type shaft

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15291 professional/industrial association specification

Specification Or Standard:

20sr class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0