

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7939>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

7.500 inches

Overall Width:

7.500 inches

First Flat Length:

0.875 inches single actuator

Flat Height:

0.467 inches single actuator

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

1.188 inches single actuator

Unthreaded Mounting Hole Diameter:

0.500 inches single mounting facility

Individual Section Quantity:

6

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6202-74224

Longest Horizontal Distance Between Mounting Centers:

5.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Threaded stud

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

20sr class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0