NSN 5930-00-548-7940

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7940

Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
7.500 inches
Overall Width:
7.500 inches
First Flat Length:
0.875 inches single actuator
Flat Height:
0.467 inches single actuator
Shaft Diameter:
0.625 inches single actuator
Shaft Length:
1.188 inches single actuator
Unthreaded Mounting Hole Diameter:
0.500 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9s5360pc6
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Threaded stud
Contact Switching Action:

Breaks before makes each section front

NSN 5930-00-548-7940

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15291/11 government specification

Specification Or Standard:

20sr2e1 type

-- - 71

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0